


## MYC-JS8MPQ System-On-Module Overview



- ✓ NXP i.MX8M Plus Quad Application Processor based on 1.6 GHz Arm Cortex-A53 and 800MHz Cortex-M7 Cores
- ✓ A Neural Processing Unit (NPU) up to 2.3 TOPS, 3D GPU
- ✓ 2GB/4GB LPDDR4, 16GB/32GB eMMC Flash, 32Kbit EEPROM
- ✓ Power Management IC (PMIC)
- ✓ Onboard Wi-Fi 6 & BT 5.4 Module
- ✓ 314-pin SMARC 2.2 Expansion Connector
- ✓ Supports Working Temperature Ranging from -40 ° C to 85 ° C
- ✓ Supports Running Linux 6.12.49





Measuring 82mm x 50mm, the MYC-JS8MPQ is a high-performance Edge AI SMARC System-on-Module (SOM) powered by the NXP i.MX 8M Plus processor. It features four Cortex-A53 cores (up to 1.6 GHz) and a Cortex-M7 core for real-time control, and a 2.3 TOPS NPU along with a 3D GPU for edge AI inference and graphics.

The MYC-JS8MPQ SOM integrates LPDDR4 (2GB/4GB), eMMC (16GB/32GB), and 32Kbit EEPROM for flexible storage options, along with onboard Wi-Fi 6 and BT 5.4 module, a Gigabit Ethernet PHY, and a USB 3.0 HUB. Security is reinforced by an independent TPM 2.0 chip and the built-in NXP i.MX 8M Plus security subsystem, while the onboard PMIC delivers efficient power management.

The 314-pin SMARC 2.2 connector offers versatile expansion options, including dual Gigabit Ethernet, multi-display outputs (HDMI, MIPI-DSI or 2x LVDS), dual MIPI-CSI camera inputs, PCIe, USB 3.0/USB 2.0 and CAN FD, as well as a full suite of UART, SPI, I2C, PWM, SDIO, and SAI interfaces for peripheral integration.


MYIR provides a complete software package including a Yocto Linux (kernel 6.12.49) BSP, open-source drivers, and documentation to accelerate time-to-market. The module is available in industrial (-40 to +85 °C) temperature grades, making it ideal for edge AI gateways, industrial automation, and machine vision, intelligent HMI systems, medical devices and power system applications.




*MYC-JS8MPQ System-On-Module (Top-view and Bottom-view)*

The MYD-JS8MPQ development board combines the MYC-JS8MPQ SOM with a carrier board via a 314-pin SMARC connector. The carrier board is universal and compatible with all MYIR SMARC SOMs. It delivers extensive evaluation interfaces, including dual Gigabit Ethernet, a Mini PCIe socket with dual Micro SIM support for 4G/5G modules, a PCIe slot for NVMe SSD, a Micro SD slot, multiple USB ports (2x USB 3.0 Host, 1x USB 2.0 Host, and 1x USB 2.0 OTG). It also features dual CAN FD, RS485, and RS232, all routed through a single Phoenix connector. For display and imaging, it supports HDMI, MIPI-DSI, and LVDS, plus two MIPI-CSI camera inputs and audio I/O. This rich I/O portfolio makes it a solid reference platform for rapid prototyping with i.MX 8M Plus solutions.

For greater development flexibility, MYIR offers optional display and camera accessories for the MYD-JS8MPQ, including the MY-MIPI101C-V2 10.1-inch MIPI display, the MY-LVDS070C 7-inch LVDS display, and the MY-CAM003M and MY-CAM005M MIPI-CSI camera modules, which provide a streamlined, ready-to-use development experience.



*MYD-JS8MPQ Development Board (Top-view)*



*MYD-JS8MPQ Development Board (Bottom-view)*




## Hardware Specification

The **MYC-JS8MPQ SOM** is using NXP's 15 x 15 mm, 0.5 mm pitch, FCBGA bare die package i.MX 8M Plus Quad Application Processor (MIMX8ML8CVNKZAB) which is among the **i.MX 8M Plus family** and features as in below tables.

| Family                 | Part Number     | Configuration                          | Temperature    |
|------------------------|-----------------|----------------------------------------|----------------|
| i.MX 8M Plus Quad      | MIMX8ML8DVNLZAB | 4x A53 (1.8Ghz), VPU, NPU, ISP         | 0°C - +95°C    |
| i.MX 8M Plus Quad      | MIMX8ML6DVNLZAB | 4x A53 (1.8Ghz), VPU, ISP              | 0°C - +95°C    |
| i.MX 8M Plus Quad Lite | MIMX8ML4DVNLZAB | 4x A53 (1.8Ghz)                        | 0°C - +95°C    |
| i.MX 8M Plus Dual      | MIMX8ML3DVNLZAB | 2x A53 (1.8Ghz), VPU, NPU, ISP         | 0°C - +95°C    |
| i.MX 8M Plus Quad      | MIMX8ML8CVNKZAB | 4x A53 (1.6Ghz), VPU, NPU, ISP, CAN-FD | -40°C - +105°C |
| i.MX 8M Plus Quad      | MIMX8ML6CVNKZAB | 4x A53 (1.6Ghz), VPU, ISP, CAN-FD      | -40°C - +105°C |
| i.MX 8M Plus Quad Lite | MIMX8ML4CVNKZAB | 4x A53 (1.6Ghz), CAN-FD                | -40°C - +105°C |
| i.MX 8M Plus Dual      | MIMX8ML3CVNKZAB | 2x A53 (1.6Ghz), VPU, NPU, ISP, CAN-FD | -40°C - +105°C |

*i.MX 8M Plus Family Application Processors*



*i.MX8M Plus Series Processor Block Diagram*



|                                                                                                                                                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ● ARM Cortex-A53, frequency up to 1.8Ghz; 800Mhz ARM Cortex-M7                                                                                                                                                                                                                |
| ● 16/32-bit DRAM interface, support LPDDR4-4000, DDR4-3200, DDR3L-1600                                                                                                                                                                                                        |
| ● x1, 8-bit NAND Flash                                                                                                                                                                                                                                                        |
| ● x2, eMMC 5.1 Flash                                                                                                                                                                                                                                                          |
| ● x3, SPI NOR FLASH                                                                                                                                                                                                                                                           |
| ● x1, PCIe Gen3                                                                                                                                                                                                                                                               |
| ● x2 USB 3.0 Type C controllers with integrated PHY (also supported USB 2.0) interfaces                                                                                                                                                                                       |
| ● x3 uSDHC interface with eMMC 5.1 compliance                                                                                                                                                                                                                                 |
| ● x2 Gigabit Ethernet controller (1x TSN-capable via ENET_QOS)                                                                                                                                                                                                                |
| ● x4 UART, x6 I2C, x3 SPI                                                                                                                                                                                                                                                     |
| ● Video Processing Unit<br>1080p60 HEVC/H.265 Main, Main 10 (up to level 5.1)<br>1080p60 VP9 Profile0,2<br>1080p60 AVC/H.264 Baseline, Main, High decoder<br>1080p60 AVC/H.264 encoder<br>1080p60 HEVC/H.265 encoder                                                          |
| ● Graphic Processing Unit<br>GC7000UL with OpenCL and Vulkan support<br>166 million triangles/sec<br>Supports OpenGL ES 1.1, 2.0, 3.0, OpenCL 1.2, Vulkan<br>GC520L for 2D acceleration                                                                                       |
| ● LCDIF Display Controller<br>Support up to 1080p60 display per LCDIF if no more than 2 instances used simultaneously, or 1x 1080p60 + 2x 720p60 if all 3 instances used simultaneously.<br>One LCDIF drives MIPI DSI<br>One LCDIF drives LVDS Tx<br>One LCDIF drives HDMI Tx |
| ● MIPI Interface<br>4-lane MIPI DSI interface<br>Two instances of 4-lane MIPI CSI interface and HDR ISP                                                                                                                                                                       |
| ● Audio<br>HiFi4 Audio DSP, SPDIF input and output, x6 SAI                                                                                                                                                                                                                    |
| ● FCBGA, 0.5mm pitch, 15x15mm                                                                                                                                                                                                                                                 |

*Features of i.MX 8M Plus Application Processor*



The MYC-JS8MPQ takes full features of the NXP i.MX 8M Plus processor and the main features are characterized as below:

### **Mechanical Parameters**

- Dimensions: 82 mm × 50 mm
- PCB Layers: 10-layer design
- Power Supply: +5V/2A
- Working temperature: -40~+85 Celsius (industrial grade)

### **Processor**

- NXP i.MX 8M Plus processor
  - 4x Cortex-A53 @1.6GHz(MIMX8ML8CVNKZAB, industrial grade)
  - 1x Cortex-M7 real-time core @800 MHz
  - Integrated 2.3 TOPS NPU for edge AI inference
  - Integrated 2D/3D GPU and 1080p VPU

### **Memory**

- 2GB/4GB LPDDR4
- 16GB/32GB eMMC
- 32Kbit EEPROM

### **Peripherals and Signals Routed to Pins**

- Onboard TPM 2.0 security chip (SPI interface)
- Onboard Wi-Fi 6 (802.11a/b/g/n/ac/ax) + Bluetooth 5.4 module (AzureWave AW-XM729)
- Power Management IC (PMIC)
- 314-pin SMARC 2.2 Expansion Connector

#### **Display & Camera**

- 1x HDMI, 1x MIPI-DSI (multiplexed with LVDS1), 2x LVDS
- 2x MIPI-CSI


#### **Ethernet & High-Speed Interfaces**

- 2x GbE MDI, 10/100/1000Mbps auto-negotiation, ETH0 with TSN support
- 1x USB 2.0 OTG + 2x USB 3.0 Host + 2x USB 2.0 Host (via USB5744 HUB)
- 1x PCIe x1 Gen3.0


#### **Industrial & Peripheral Interfaces**

- 2x CAN FD
- 4x UART
- 2x SPI
- 5x I2C
- 1x SD/SDIO 3.0
- 3x PWM
- 2x SAI (audio)

*Note: the peripheral signals brought out to the expansion interface are listed in maximum number. Some signals are reused. Please refer to the processor datasheet and the SOM pinout description file.*



MYC-JS8MPQ Function Block Diagram



MYD-JS8MPQ Function Block Diagram



## Software Features

The MYC-JS8MPQ System-On-Module is fully compatible with Linux OS and comes with a complete set of software packages. To help clients accelerate their projects, the source code for the kernel and various peripheral drivers is included. The main software features are summarized below:

| Item        | Features        | Description                                         | Source Code |
|-------------|-----------------|-----------------------------------------------------|-------------|
| Bootloader  | U-boot          | Boot program uboot_2025.04                          | YES         |
| Kernel      | Linux kernel    | Customized based on official kernel_6.12.49 version | YES         |
| Drive       | USB HOST/OTG    | USB HOST/OTG drive                                  | YES         |
|             | Ethernet        | YT8531SH driver                                     | YES         |
|             | RS232           | RS232 driver                                        | YES         |
|             | RS485           | RS485 driver                                        | YES         |
|             | CAN             | CAN driver                                          | YES         |
|             | RTC             | RTC driver                                          | YES         |
|             | GPIO            | GPIO driver                                         | YES         |
|             | WIFI            | AW-XM729 driver                                     | YES         |
|             | BT              | AW-XM729 driver                                     | YES         |
|             | 4G              | EM05-CE driver                                      | YES         |
|             | 5G              | RM500Q-CN driver                                    | YES         |
|             | LVDS            | LT8912 driver                                       | YES         |
|             | MIPI DSI        | MIPI DSI driver                                     | YES         |
|             | HDMI            | HDMI driver                                         | YES         |
|             | MIPI CSI        | Camera driver                                       | YES         |
|             | Audio           | ES8388 driver                                       | YES         |
|             | Micro SD        | SD card storage driver                              | YES         |
|             | TPM2.0          | TPM driver                                          | -           |
| File system | myir-image-full | Yocto-based image with GUI support                  | YES         |

### *MYC-JS8MPQ Software Features*



## Order Information

| Product Item                                                                                                                                                                                                                                                                                                                                                                                                                    | Part No.                | Packing List                                                                                                                                                                                                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MYC-JS8MPQ<br>System-On-Module                                                                                                                                                                                                                                                                                                                                                                                                  | MYC-JS8MPQ-16E2D-160-I  | ✓ One MYC-JS8MPQ SOM<br>(Heatsink not included)                                                                                                                                                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 | MYC-JS8MPQJ-32E4D-160-I |                                                                                                                                                                                                                                        |
| MYD-JS8MPQ<br>Development Board                                                                                                                                                                                                                                                                                                                                                                                                 | MYD-JS8MPQ-16E2D-160-I  | ✓ One MYD-JS8MPQ Board<br>(Includes MYC-JS8MPQ SOM with<br>pre-installed heatsink)<br>✓ One 12V/2A Power Adapter<br>✓ One USB Type-A to Type-C cable<br>✓ One Quick Start Guide<br>✓ One Wi-Fi IPEX antenna<br>✓ One Wi-Fi rod antenna |
|                                                                                                                                                                                                                                                                                                                                                                                                                                 | MYD-JS8MPQ-32E4D-160-I  |                                                                                                                                                                                                                                        |
| MY-MIPI101C-V2<br>10.1-inch LCD Module                                                                                                                                                                                                                                                                                                                                                                                          | MY-MIPI101C-V2          | ✓ MY-MIPI101C-V2 10.1-inch MIPI LCD<br>Module with Capacitive Touch Screen                                                                                                                                                             |
| MY-LVDS070C<br>7-inch LCD Module                                                                                                                                                                                                                                                                                                                                                                                                | MY-LVDS070C             | ✓ MY-LVDS070C 7-inch LVDS Display<br>Module with Capacitive Touch Screen                                                                                                                                                               |
| MY-CAM003M<br>MIPI Camera Module                                                                                                                                                                                                                                                                                                                                                                                                | MY-CAM003M              | ✓ MY-CAM003M MIPI Camera Module                                                                                                                                                                                                        |
| MY-CAM005M<br>MIPI Camera Module                                                                                                                                                                                                                                                                                                                                                                                                | MY-CAM005M              | ✓ MY-CAM005M MIPI Camera Module                                                                                                                                                                                                        |
| <p><i>Note:</i></p> <p>1. One MYD-JS8MPQ Development Board comprises one MYC-JS8MPQ SOM mounted onto the base board. If you require additional SOMs, you may place order for extras.</p> <p>2. Bulk discounts are available. Please contact MYIR for inquiries.</p> <p>3. We accept custom design based on the MYD-JS8MPQ, whether reducing, adding or modifying the existing hardware according to customer's requirement.</p> |                         |                                                                                                                                                                                                                                        |



### MYIR Electronics Limited

Headquarter Address: Room 04, 6th Floor, Building No.2, Fada Road, Yunli Smart Park, Bantian, Longgang District, Shenzhen, Guangdong, China 518129

Factory Address: Room 201, Block C, Shengjianli Industrial Park, Dafu Industrial Zone, Guanlan, Longhua District, Shenzhen, 518110, China

Website: [en.myir.cn](http://en.myir.cn)

Email: [sales@myir.cn](mailto:sales@myir.cn)

Tel: +86-755-22984836